



Material Safety Data Sheet

SECTION 1 – IDENTIFICATION

Revision Date:	December of 2020.
Product Name:	Calcium Hypochlorite, Hydrated.
Catalog Numbers:	AC199030010
Synonyms:	Calcium Oxychloride; Bleaching Powder; Calcium Salt; Chlorinated Lime
CAS Registry Number:	7778-54-3
EC No.:	231-908-7
PIN (UN/NA Number(s)):	2880
RTECS Number(s):	NH3485000
Chemical Family:	Salt of hypochlorous acid
Molecular Formula:	Ca-Cl ₂ -O ₂
Structural Formula:	Ca(OCl) ₂
Product Uses:	Water-treatment Agent, Bleaching Agent (paper, textiles), Bactericide, Algicide, Algicide, Deodorant, Potable Water Purification, Disinfectant for Swimming Pools, Fungicide.
Contact Information:	
Company Name:	KUNMING FORTUNE STAR TRADING CO., LTD.
Address:	1-3-1102, GUIXIN GARDEN, NO. 442, NORTH HAIYUAN ROAD, WUHUA DISTRICT KUNMING, YUNNAN, CHINA
Tel:	+86 871 68397667

Emergency Phone Numbers: +86-13700618170

SECTION 2 – HAZARDOUS IDENTIFICATION

Appearance:	White solid; products may have a strong chlorine odour resulting from decomposition of calcium hypochlorite.
Classified	as Dangerous Goods According to Regulation (EC) No. 1272/2008 (CLP/GHS) and Echa's Directive 67/548/EEC.
Danger Overview:	OXIDIZING CORROSIVE DANGEROUS FOR THE ENVIRONMENT.
<u>Risk Phrases:</u>	
R8	Contact with combustible material may cause fire.
R31	Contact with acids liberates toxic gas.
R34	Causes burns.
R22	Harmful if swallowed.
R50	Very toxic to aquatic organisms.
<u>Safety Phrases:</u>	
S1/2	Keep locked up and out of the reach of children.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61	Avoid release to the environment. Refer to special instructions / Material Safety Data Sheets.



Labelling according to Regulation (EC) No.1272/2008 (CLP/GHS)



DANGEROUS FOR THE ENVIRONMENT



OXIDIZING



CORROSIVE



SECTION 3 – COMPOSITION / INGREDIENT INFORMATION

Ingredients

<u>Chemical Entity</u>	<u>CAS Number</u>	<u>Proportions (%)</u>
Calcium Dihypochlorite	[7778-54-3]	> 65.0
Sodium Chloride	[7647-14-5]	< 25.0
Calcium Dichloride	[10043-52-4]	< 6.0
Water	[7732-18-5]	< 10.0
Calcium Dihydroxide	[1305-62-0]	< 6.0
Calcium Carbonate	[471-34-1]	< 4.0
Note: Available Chlorine		≥ 65.0
Granular Size (14-50Mesh)		≥ 90.0
Water Insoluble		< 6.0

SECTION 4 – FIRST AID MEASURES

Description of necessary measures according to routes of exposure.

Swallowed	Rinse mouth with water. Give water to drink provided victim is conscious. Do NOT induce vomiting. If vomiting occurs naturally, rinse mouth and repeat administration of water. Seek medical attention immediately.
Eye	Immediately flush eyes with water for at least 20-30 minutes. Neutral saline solution may be used as soon as it is available. Do NOT interrupt flushing. Take care not to rinse contaminated water into the non-affected eye or onto the face. Seek immediate medical attention.
Skin	Immediately flush skin with water for at least 20-30 minutes. Do NOT interrupt flushing. Under running water, remove contaminated clothing. Discard contaminated leather goods. Transport to the nearest medical facility for treatment.
Inhaled	Remove victim from exposure to fresh air. If breathing is difficult give oxygen. Do NOT use mouth to mouth respiration. If breathing has ceased, apply artificial respiration using oxygen and a suitable mechanical device such as a bay and a mask. Seek immediate medical assistance.
Advice to Doctor	Treat symptomatically based on individual reactions of patient and judgement of doctor. Effects may be delayed. May cause corneal burns.

Aggravated medical conditions caused by exposure

Persons with pre-existing skin, eye, tooth, or respiratory disorders, or with seasonal allergic rhinitis may be more susceptible to the effects of this material.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

SMALL FIRE: Use flooding quantities of water. Do NOT use dry chemicals, carbon dioxide or foam. If safe to do so, move undamaged containers from fire area. Do NOT move cargo if cargo has been



exposed to heat.

LARGE FIRE: Flood area with water from a protected position. Cool containers with flooding quantities of water until well after fire is out. If impossible, withdraw from area and let fire burn. Avoid getting water inside containers: a violent reaction may occur. Dam fire control water for safe disposal.

Hazards from Combustion Products

Powerful oxidizing solid. Will accelerate burning when involved in a fire. This strong oxidiser may cause a fire as it contacts with combustible materials. Containers may explode when heated. Incompatible with flammable, organic and combustible materials, ammonia, primary amines, aromatic amines, and urea acids, ammonium chloride, different types of chlorinating chemicals, ethanol or methanol, hydroxy compounds, acetylene, acetic acid and potassium cyanide, reducing agents, metal oxides, charcoal + heat, metals, organic sulfur compounds, sulfur (damp), turpentine and all sources of ignition. When involved in a fire, this product may generate irritating and highly toxic gases of hydrogen chloride gas, hydrochloric acid, calcium oxides, calcium chlorate, calcium hydroxide, calcium carbonate, and chlorine, oxygen gas, and dichlorine monoxide above 158°C.

Special Protective Precautions and Equipment for Fire Fighters

Fire fighters should wear a positive-pressure self-contained breathing apparatus and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots and gloves). Clear fire area of all non-emergency personnel. Stay upwind. Keep out of low areas. Eliminate ignition sources.

Flammability Conditions

Non combustible solid. Strong oxidiser and its heat of reaction with reducing agents, contaminants or combustibles may cause ignition. Explosions involving calcium hypochlorite have occurred. Product will cause a severe increase in the burning rate of combustible materials with which it comes into contact or that will undergo vigorous self-sustained decomposition due to contamination or exposure to heat.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Personnel involved in the clean up should wear full protective clothing. Evacuate all unnecessary personnel. Eliminate all sources of ignition. Increase ventilation. Avoid generating dust. Stop leak if safe to do so. Isolate the danger area. Do NOT let product reach drains or waterways. If product does enter a waterway, advise the Environmental Protection Authority or your local Waste Management. Use clean, non-sparking tools and equipment.

Methods and Materials for Containment and Clean Up

Contain and sweep/shovel up spills with dust binding material or use an industrial vacuum cleaner. Transfer to a suitable, labelled container and dispose of promptly as hazardous waste.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling

Ensure an eye bath and safety shower are available and ready for use. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling. Take precautionary measures against static discharges by bonding and grounding equipment. Avoid contact with eyes, skin and clothing. Do not inhale product dust/fumes. Do NOT allow product to get damp. Do NOT mix with other chemicals. Do NOT add water to the product - add the product to the water. Use only clean utensils for handling as remnants of other products may cause a violent reaction leading to fire or explosion.



Conditions for Safe Storage (Including Any Incompatibles)

Store in a cool, dry, well-ventilated area. Keep containers tightly closed when not in use. Inspect regularly for deficiencies such as damage or leaks. Protect against physical damage. Store away from incompatible materials such as flammable, organic and combustible materials, ammonia, primary amines, aromatic amines, and urea acids, ammonium chloride, different types of chlorinating chemicals, ethanol or methanol, hydroxy compounds, acetylene, acetic acid and potassium cyanide, reducing agents, metal oxides, charcoal + heat, metals, organic sulfur, compounds, sulfur (damp), turpentine and all sources of ignition. Protect from direct sunlight, moisture, food and feedstuffs. Avoid storage in wood floors. Store and transport in an upright container. The bulk material may ignite or explode in storage. Traces of water may initiate the reaction. Store in an area without drain or sewer access. Store below 50°C to avoid slow decomposition, room temperature recommended. This product has a UN Classification of 2880 and a Dangerous Goods Class 5.1 Oxidiser according to The Australian Code for the Transport of Dangerous Goods By Road and Rail.

Container Type

Packaging must comply with requirements of Hazardous Substances (Packaging) Regulations. Store in original packaging as approved by manufacturer. SUITABLE: A plastic or fibreboard drum using a strong polyethylene chloride inner package.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards

No exposure standard has been established for this product. However, the exposure standard for dust not otherwise specified is 10mg/m³ (for inspirable dust) and 3mg/m³ (for respirable dust). A time weighted average (TWA) has been established for chlorine (worksafe Aust) of 3mg/m³, (1ppm) (Peak Limitation). The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8hr working day for a 5 day working week. Peak Limitation: a ceiling concentration which should not be exceeded over a measurement period which should be as short as possible but not exceeding 15 minutes.

Biological Limit Values

No information available on biological limits for this product.

Engineering Controls

A system of local and/or general exhaust is recommended to keep employee exposures as low as possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

Personal Protection

RESPIRATOR: Wear an approved positive pressure, full-facepiece where engineering controls are inadequate.
EYES: Wear a full face shield or chemical goggles.
HANDS: Vinyl gloves are recommended.
CLOTHING: Flame-retardant coveralls and anti-static footwear.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White to Gray Powder or Crystalline Granule
Formula	Ca(ClO) ₂
Odour	Strong Chlorine Odour
Vapour Pressure	Not applicable.
Vapour Density	6.9
Boiling Point	Decomposes deg C
Melting Point	Approx. 100°C deg C



Solubility in Water	21g/100mL (25°C); 43-48g/100ml (40°C)
Specific Gravity	2.00 (20°C) (Water = 1)
Flash Point	Not applicable.
pH	10.8 (10% Solution)
Lower Explosion Limit	Not applicable.
Upper Explosion Limit	Not applicable.
Ignition Temperature	Not applicable.
Specific Heat Value	Not applicable.
Particle Size	Not applicable.
Volatile Organic Compounds (VOC) Content	Not applicable.
Evaporation Rate	Not applicable.
Viscosity	Not applicable.
Percent Volatile	0% Vol (21°C)
Octanol/Water partition coefficient	Log P(oct) -2.46
Saturated Vapour Concentration	Not applicable.
Additional Characteristics	Not applicable.
Flame Propagation/Burning Rate of Solid Materials	Not applicable.
Properties of Materials That May Initiate or Contribute to Fire Intensity	Fire accelerant
Potential for Dust Explosion	Not applicable.
Reactions that Release Flammable Gases	Not applicable.
Fast of Intensely Burning Characteristics	Will accelerate burning when involved in a fire. Non-flammables That Could Contribute Unusual Hazards to a Fire Not applicable.
Release of Invisible Flammable Vapours and Gases	Not applicable.
Decomposition Temperature	100 deg C; slowly decomposed less than 100 deg C; when above 158 deg C, around 12 minutes of heating up, violent decomposition and combustion occur;
Additional Information	Odour Threshold: 1-3ppm (Value for chlorine) Refractive Index: 1.545 (alpha), 1.69 (beta) Bulk Density: 1.0g/cm ³ (loose granules) Moisture content: 5.5-10% Molecular Weight: 142.98 Solubility: Insoluble in ethanol

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability:

Thermically stable when stored and used as directed. May decompose violently if exposed to heat or direct sunlight. All hypochlorite solutions are unstable and slowly decompose on contact with air, especially if acidified, or contaminated. Decomposition may lead to spontaneous ignition through self- heating.



Condition to Avoid:

Avoid excessive heat, elevated temperatures, sunlight, flame, sources of ignition and shock, dust generation, moisture/high humidity, contamination with combustible materials, acidic conditions, the presence of metals and other impurities.

Incompatibility Material:

Incompatible with flammable, organic and combustible materials, ammonia, primary amines, aromatic amines, and urea acids, ammonium chloride, different types of chlorinating chemicals, ethanol or methanol, hydroxy compounds, acetylene, acetic acid and potassium cyanide, reducing agents, metal oxides, charcoal + heat, metals, organic sulfur, compounds, sulfur (damp), turpentine and all sources of ignition.

Hazardous Reactions:

Hazardous Polymerisation will not occur, however this product is a highly reactive oxidising chlorine compound. May cause fire or explosion. Readily ignites with flammable and combustible materials, in contact with anhydrous (dry) calcium hypochlorite. Reacts with ammonia, primary amines, aromatic amines, and urea to form explosive nitrogen trichloride. May explode upon contact with ethanol or methanol, due to the formation of the alkyl hypo-chlorites. Contact with hydroxy compounds causes ignition and may be explosive. Contact of acetylene may lead to formation of explosive chloroacetylenes. Reaction with acetic acid and potassium cyanide may be explosive. Reaction with reducing agents causes a violent reaction. Reaction with metal oxides can cause a violent oxygen-evolving decomposition of hypochlorites. A confined intimate mixture of calcium hypochlorite + finely divided charcoal exploded on heating. Metals catalyze the decomposition. Reaction with organic sulfur compounds may cause a flash fire/explosion. A mixture of damp sulfur and 'solid swimming pool chlorine' caused a violent exothermic reaction. May explode with turpentine.

SECTION 11 – TOXICOLOGICAL INFORMATION**Toxicity Data**

Oral LD50 Rat: 850mg/Kg Dermal LD50 Rabbit: >2000mg/Kg (40% water solution) Carcinogenicity: Hypochlorite salts are evaluated in the IARC monographs as Group 3: Not Classifiable as to carcinogenicity to Humans. Mutagenicity: Calcium Hypochlorite was mutagenic in bacteria and cultured mammalian cells. Mutation in microorganisms, Bacteria - Salmonella typhimurium: 1mg/plate Cytogenetic analysis, hamster fibroblast: 4mg/L Eye Irritation Test: Rabbit, dosage: equivalent to 0.1mg/volume-70mg sample: Results: Corrosive injury. Rabbit, dosage: 5% solution/30 seconds followed by rinsing with water. Results: Superficial injury. Within one day injury had healed almost completely. Skin Irritation: 0.5mg moistened with water/24hrs: Corrosive injury.

Health Effects – Acute**Swallowed**

Harmful if swallowed. Corrosive. Calcium hypochlorite can react with organic material and stomach acids to release chlorine gas, which can cause vomiting, difficulty breathing and chemical injury to the respiratory tract and lungs. Ingestion of calcium hypochlorite solid or solutions can cause severe burns to the mouth, throat and stomach, sore throat, swelling of the throat, severe and permanent damage and perforation of the digestive tract and stomach with immediate pain, gastrointestinal symptoms, nausea, vomiting, diarrhoea, abdominal pain, convulsions, delirium, coma, respiratory collapse, and possible death. As little as 1 ounce may be lethal. Concentrations lower than 15% available chlorine can also be lethal.

Eye

Solid and solutions are corrosive, and can cause permanent eye damage, including blindness. Dust may cause irritation of the inner eyelids and injury to the cornea (ulcers). Solutions release corrosive chlorine gas at normal temperatures. The amount of chlorine gas released depends on the concentration of the solution, pH, temperature, ionic strength, exposure to light and the presence of metals and other impurities. Airborne chlorine can produce severe eye irritation at concentrations of 1ppm and above. Prolonged or repeated eye contact may cause conjunctivitis. Effects may be delayed.



Skin

Solutions are corrosive and can cause burns, blisters, and permanent scarring. Dusts will form concentrated solutions on wet or sweaty hands. The irritation hazard increases with increasing concentration of the solution and duration of contact. May be harmful if absorbed through the skin. With severe exposures, death could result. Prolonged or repeated skin contact may cause dry, red, itchy, cracked skin (dermatitis).

Inhaled

May be harmful if inhaled. Dust may cause severe irritation and injury to the nasal passages including tissue death (necrosis) and injury to the throat (laryngeal oedema) and upper respiratory tract. Solid calcium hypochlorite decomposes and releases corrosive chlorine gas. Depending on the concentration, chlorine gas can cause nose throat and respiratory tract irritation and or severe lung injury and death. Mists formed from solutions may be moderately to severely irritating. Symptoms of exposure include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting. Inhalation may be fatal as a result of spasm inflammation and oedema of the larynx and bronchi, chemical pneumonitis and pulmonary oedema.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity

No data available.

Persistence and Degradability

No information available on persistence/degradability for this product. Mobility Soluble in water: 21g/100mL (25°C)

Environmental Fate (Exposure)

Do NOT allow product to reach waterways, drains, or sewers.

Bioaccumulative Potential

No information available on bioaccumulation for this product.

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal

Dispose of in accordance with all local, state and federal regulations. All empty packaging should be disposed of in accordance with Local, State, and Federal Regulations or recycled/reconditioned at an approved facility.

Special Precautions for Land Fill or Incineration

Contact a specialist disposal company or the local waste regulator for advice. This should be done in accordance with 'The Hazardous Waste Act'. This material may be suitable for secure landfill.

SECTION 14 – TRANSPORT INFORMATION

Land Transport (China)

UN Number	2880
Shipping Name	CALCIUM HYPOCHLORITE, HYDRATED
Dangerous Goods Class	5.1 Oxidising Agent (not an organic peroxide)
Subsidiary Risk	Not applicable.
Pack Group	II
Precaution for User	OXIDIZING CORROSIVE DANGEROUS FOR THE ENVIRONMENT



Special Provision

Not applicable.



Sea Transport

UN Number

2880

Shipping Name

CALCIUM HYPOCHLORITE, HYDRATED

Dangerous Goods Class

5.1 Oxidising Agent (not an organic peroxide)

Subsidiary Risk

Not applicable.

Pack Group

II

Precaution for User

OXIDIZING CORROSIVE DANGEROUS FOR THE ENVIRONMENT

Special Provision

Not applicable.



SECTION 15 – REGULATORY INFORMATION

Classified as Dangerous Goods According to Regulation (EC) No. 1272/2008 (CLP/GHS) and Annex I European Directive 67/548/EEC. EINECS No: 231-908-7 Calcium Hypochlorite

Poisons Schedule Under Chinese Standard GB/T 10666-2008 for Calcium Hypochlorite

SECTION 16 – OTHER INFORMATION

Legend to Abbreviations and Acronyms

CAS: Chemical Abstracts Service (Registry Number)

IDLH: Immediately Dangerous to Life and Health

IMDG: International Maritime Dangerous Goods Code



LC50: LC stands for lethal concentration. LC50 is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours.

LD50: LD stands for Lethal Dose. LD50 is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals

PEL: Permissible Exposure Limit

ppm/6h: parts per million per 6 hours

RCP: Reciprocal Calculation Procedure

STEL: Short Term Exposure Limit

TLV: Threshold Limit Value

TWA: Time Weighted Average

ug/24H: micrograms per 24 hours

SECTION 17 – DISCLAIMER

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Hongkong Freebarque Development Limited be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.